

kränzle® KTH895-1-QC



2,830 psi



15 L/min



415V, 20A



Top of the range 415V Hot Water high pressure cleaner in terms of safety, performance, reliability and low cost of operation. Ideal for regular use in applications like heavy machinery, transport and manufacturing plants. Features - Pressure 2830psi, 15 L/min cleaning power, Hot Water up to 150° temperature to destroy grease and grime.

20Mtr HP Hose and integrated hose reel + folding crank

Total stop System + Safety cut-out

Digital operating panel control temperature + operating hours

Tidy storage system for practical stowing of accessories

Low fuel cut-off for burner + Digital thermostat

Digital thermostat + safety thermostat

Parking brake for secure stationary position

Made in Germany

4 large rubber tyred wheels

High pressure detergent intake/application



Technical Data

Operating pressure adjustable 2,830 psi	Power supply cable 7.5m
Max. admissible overpressure 3,120 psi	(LxWxH) 1,050 x 800 x 1,300 mm
Connected Load 415V, 20A	Weight 223Kg
Motor speed 1400 rpm	Hose reel + HP Hose 20m
Water Output 15Ltr/Min	Trigger Gun with safety catch
kW Power Output 5.5	S/S Lance with fan-jet Nozzle 045
Water tank volume 12.4Ltr	DN12 Quick release connector system
Hot water output adjustable 12-86°C	4 way safety system
Steam Level 155°C	Overload protection
Heating Output 5kW	Tidy storage system
Fuel tank 35Ltr	5 Year Commercial Warranty



For more information
please visit our website

P 1800 812 223

E sales@powerblast.com.au

W www.powerblast.com.au