

HOT WATER

ndustrial Model - Three Phase



2,400 psi



19.4L/min





The Kranzle KTH1165-1 is the top of the range 415V Hot Water high pressure cleaner in terms of safety, performance, reliability and low cost of operation. Ideal for regular use in applications like heavy machinery, transport and manufacturing/food processing industry. High flow rates are ideal for flushing away mud etc.



Tidy storage system for accessories

Low fuel cut-off for burner + safety thermostat

Overload protection

Removable covers for ease of access

4 large rubber tyred
Made wheels + parking brake

■ in ■ Germany

Germany



20mtr HP Hose + HP Hose Reel + folding crank

Digital operating panel, to control the temperature + operating time management

High pressure detergent

10 Year Warranty on Brass Pump Head

Technical Data

Operating pressure adjustal	ble 2,400 psi
Max. admissible overpressu	ıre 2,610psi
Connected Load	415V, 20A
Motor speed	1400 rpm
Water Output	19.4Ltr/Min
kW Power Output	5.0kW
Water tank volume	12Ltr
Hot water output adjustable	e 12-82°C
Steam Level	155°C
Heating Output	78kW
Fuel tank	35Ltr

Digital thermostat + safety thermostat		
Power supply	cable cable	7.5m
(LxWxH)	1,050 x 80	0 x 1,300 mm
Weight		223Kg
Hose reel + H	P Hose	20m
Trigger Gun with safety catch		
S/S Lance with fan-jet Nozzle 07		
DN12 Quick release connector system		
4 way safety system		
5 Year Commercial Warranty		
10 Year warranty on brass pump head		







P 1800 812 223

E sa

sales@powerblast.com.au



www.powerblast.com.au